

AD-A134 429

EXPERIMENTAL STUDY OF A DIELECTRIC ANTENNA AT THE
FREQUENCY RANGE OF 76-80 GHZ(U) ILLINOIS UNIV AT URBANA
ELECTROMAGNETICS LAB A CHANG ET AL. OCT 83 UIEM-83-12


1/1

UNCLASSIFIED

F/G 9/1

NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AD-A134429

ARO 18054.7-EL

EXPERIMENTAL STUDY OF A DIELECTRIC ANTENNA
AT THE FREQUENCY RANGE OF 76-80 GHZ

12

INTERIM TECHNICAL REPORT

A. Chang
R. Mittra

October 1983

SUPPORTED IN PART BY
U. S. ARMY RESEARCH OFFICE
GRANT NO. DAAG29-82-K-0084



DTIC
ELECTE
NOV 7 1983
S B

ELECTROMAGNETICS LABORATORY
DEPARTMENT OF ELECTRICAL ENGINEERING
ENGINEERING EXPERIMENT STATION
UNIVERSITY OF ILLINOIS AT URBANA-CHAMPAIGN
URBANA, ILLINOIS 61801

DTIC FILE COPY

APPROVED FOR PUBLIC RELEASE.
DISTRIBUTION UNLIMITED.

83 11 07 032

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) EXPERIMENTAL STUDY OF A DIELECTRIC ANTENNA AT THE FREQUENCY RANGE OF 76-80 GHZ		5. TYPE OF REPORT & PERIOD COVERED Interim Technical Report
7. AUTHOR(s) A. Chang R. Mittra		6. PERFORMING ORG. REPORT NUMBER EM 83-12; UILU-ENG-83-2557
9. PERFORMING ORGANIZATION NAME AND ADDRESS Electromagnetics Laboratory Department of Electrical Engineering University of Illinois, Urbana, Illinois 61801		8. CONTRACT OR GRANT NUMBER(s) Supported in part by DAAG29-82-K-0084
11. CONTROLLING OFFICE NAME AND ADDRESS U. S. Army Research Office P. O. Box 12211 Research Triangle Park, N.C. 27709		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS P18054-EL
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE October 1983
		13. NUMBER OF PAGES 15
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Distribution Unlimited. Approved for public release.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) dielectric rod antennas; millimeter waves; optimal design; coupling to dielectric waveguides		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The study of the shape and transition of an antenna at high frequency is a fundamental problem to be considered in its design if a reasonable performance is to be expected. Some experimental results are given regarding shape and transition at 76-80 GHz.		

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 68 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

Electromagnetics Laboratory Report No. 83-12

EXPERIMENTAL STUDY OF A DIELECTRIC ANTENNA
AT THE FREQUENCY RANGE OF 76-80 GHZ

by

A. Chang
R. Mittra

Electromagnetics Laboratory
Department of Electrical Engineering
University of Illinois at Urbana-Champaign
Urbana, Illinois 61801

Interim Technical Report

October 1983

Supported in part by

U. S. Army Research Office
Contract No. DAAG29-82-K-0084

TABLE OF CONTENTS

	Page
I. INTRODUCTION.	1
II. EXPERIMENTS ON THE TRANSITIONS OF ANTENNA	2
III. EXPERIMENTS OF THE SHAPES OF ANTENNA.	6
IV. CONCLUSION.	11
REFERENCES.	12

Accession For	
NTIS	<input checked="" type="checkbox"/>
PLAS T-4	<input type="checkbox"/>
Unclassified	<input type="checkbox"/>
Justified	<input type="checkbox"/>
By	
Distribution/	
Availability Codes	
Avail and/or	
Dist	Special
A-1	

3510
8077
100-1-1


I. INTRODUCTION

The utilization of higher frequencies (s.h.f. or e.h.f. range) in the millimeter-wave integrated circuits has been of a constant interest to designers in this field. In designing an antenna which is useful in the microwave frequencies, the application of dielectric materials to improve the gain-radiation characteristic is becoming a common practice. However, the problems concerning the shape of a dielectric antenna and the transition from the metal waveguide to the antenna need careful attention if its maximum effectiveness is to be achieved. A dielectric wedge-shaped waveguide antenna at 8.5-11.5 GHz frequency range has been investigated recently [1]. In this report the usefulness of the wedge-shaped antenna at the higher frequency range of 76-80 GHz is examined. Other shapes than the wedge together with various transition types are considered. At millimeter wavelengths, it is desired to devise a transition which is as short as possible and with an acceptably small insertion loss. Thus, whenever transition is concerned, special attention has been paid to achieve these criteria. The dielectric material used is rexolite.


II. EXPERIMENTS ON THE TRANSITIONS OF ANTENNA

Figure 1 shows the shapes and the terms used to describe a particular shape. One surprising result obtained from experimenting with various types of transitions is the fact that the types of tapering or even the length of the transition affect the antenna pattern very little, if any at all. Refer to Fig. 2 and Fig. 3 for the patterns taken for wedge-shaped transition and abrupt transition, respectively, as the length (L_t) is varied. While L_t changed, the parameters L_a and L_w were kept constant for each case. Contrary to the usual thought and some other experiments performed earlier which showed the effect of transition [2] on the gain-radiation pattern, the experiment has shown that, regardless of the type and length of the transition from metal waveguide to the antenna, it is possible to obtain almost identical gain-radiation patterns provided that the parameters L_a and L_w are kept constant—at least, at the frequency range of 76-80 GHz. It is quite interesting to see that not only do we not need a smooth transition but need to have just enough L_t to attach the dielectric antenna to the waveguide so that it will adhere to it.


(a) wedge-shaped antenna




(b) rod-shaped antenna



(c) wedge transitron



(d) abrupt transitron



(e) rod transitron




Figure 1 H-plane view.

L_{AW}, L_{A1}

(4)




Figure 3. Radiation pattern for abrupt-transition.

III. EXPERIMENTS ON THE SHAPES OF ANTENNA

Unless indicated explicitly otherwise, the patterns are made in the H-plane. But the experiment performed in the E-plane has shown that E-plane patterns have similar gain-radiation characteristics to those in the H-plane.

Having established the fact that the transition has little influence, it has been verified that the antenna patterns are just about the same whether it be a wedge-shaped or a rod-shaped antenna. Refer to Fig. 4. But the experiment indicates that the relative lengths of L_a and L_w are the factors to determine the gain and the half-power beamwidth characteristics of each type under examination. After many trial-and-error types of experiments, it was found that the difference $L_a - L_w$ should be about 1.5λ or less to obtain reasonably good gain characteristics.

As the frequency changes over the 76-80 GHz range, the radiation pattern shows a slight but not too significant difference (usually within 0.5-1.0 dB difference over the 76-80 GHz range).

As for the shape chosen for the antenna, it is of some interest to a designer to know how the shape affects the pattern. Experiments were performed for this purpose at 77.5 GHz. The results are quite interesting. Various types which may be considered arbitrary are shown, together with the patterns obtained, in Fig. 5. Notice that as long as the antenna is essentially "straight" and the difference $L_a - L_w$ is within approximately 1.0 to 1.5λ , roughly, the gain characteristic is good enough to match

$I = 180 \text{ mA}$




Figure 4. Radiation patterns of different antenna shapes with the same wedge-transition.




Figure 5a. Straight asymmetric antenna with wedge transition.




Figure 5b. Straight symmetric antenna with abrupt transition.

the patterns obtained from well-made, symmetric antennas. Thus, it is quite doubtful if a specific shape must be used to obtain a reasonable performance of a dielectric antenna at the frequency range of 76-80 GHz.

IV. CONCLUSION

Shapes of a dielectric antenna and its transition to the metal waveguide were examined to obtain the maximum effectiveness of the antenna. It is found that "any" type of transition is fine with "any" length. To obtain a reasonable pattern, i.e., good gain and HPBW, the shape of the antenna could be quite arbitrary, as long as certain requirements for L_a and L_w are met. The usual gain obtained is around 16 dB and HPBW of 20-25 degree.

REFERENCES

- [1] K.K.S. Jamwal, A. Dhar, Renu Vakil, "Analysis, design and characteristics of X-band dielectric wedge waveguide antennas," pp. 99-102, Microwave J., December 1982.
- [2] T. N. Trinh, J.A.G. Malherbe and R. Mittra, "A metal-to-dielectric waveguide transition with application to millimeter-wave integrated circuits," 1980 IEEE MTT-S International Microwave Symposium, in Washington, D.C., pp.205-207, May 1980.

END

FILMED

EDITION